


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>G09F 3/18, G06K 19/077</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/22603</b> <b>(43) International Publication Date:</b> 20 April 2000 (20.04.00)
<b>(21) International Application Number:</b> PCT/EP99/07571 <b>(22) International Filing Date:</b> 8 October 1999 (08.10.99) <b>(30) Priority Data:</b> 198 47 194.7 ✓ 13 October 1998 (13.10.98) DE <b>(71) Applicant (for all designated States except US):</b> SCHREINER ETIKETTEN UND SELBSTKLEBETECHNIK GMBH & CO. [DE/DE]; Bruckmannring 22, D-85764 Oberschleis- heim (DE). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> SCHREINER, Helmut [DE/DE]; Schillerstrasse 23, D-85757 Karlsfeld (DE). <b>(74) Agent:</b> GÜNTHER, Kehl; Friedrich-Herschel-Strasse 9, D-81679 München (DE).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> With international search report.
<b>(54) Title:</b> LABEL    <b>(57) Abstract</b>  The present invention relates to a label comprising at least one electronic component (2), wherein the electronic component (2) is cast in synthetic material (1). The label may be at least partially provided with adhesive (4) on at least one side.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Label

5

The present invention relates to a label comprising at least one electronic component.

10

These days, labels incorporating electronic components are used, inter alia, in those fields where one is concerned with the protection of goods from theft. Hereby, one or more electronic components are disposed within the label for setting off an alarm when they pass through an electromagnetically, or otherwise, actuated barrier, that is, insofar as the label has not been previously deactivated, for example, when paying for the goods at the cash desk.

20

In this connection, there is a not infrequently occurring, serious problem that the usually highly sensitive electronic components are disposed in the labels or on the labels such that they are more or less unprotected. Since the labels themselves are usually made of less robust materials such as paper, the electronic components are not infrequently the subject of unintentional or deliberate damage which thereby puts the wanted function of the electronic components out of action.

30

Based upon the aforementioned disadvantages and shortcomings of the known labels, the object of the present invention is to provide a label comprising at least one electronic component wherein the electronic component is protected by and retained securely on the label.

35

In accordance with the invention, this object is achieved by means of a label comprising at least one electronic component, whereby, in the case of the label according to the teaching of the present invention, the electronic component is cast in synthetic material.

Surprisingly, a label formed in this manner is exceptionally insensitive to damage since the electronic component is securely retained in and protected by the synthetic material.

In this connection, the skilled person will particularly appreciate that the label in accordance with the present invention can be employed not just for protecting against theft but may also be employed, for example, for locating and/or detecting the presence or absence of an object such as when one is faced with the problem of determining the current location of an object that is being sought. Here, objects with which a label of this type can be employed may perhaps be files, rubbish containers or palettes that present a logistical problem which can be solved by the present invention in an advantageous manner.

In addition, the present invention is also suitable for use in a system for storing and transmitting data in non-contact making manner between an object (one of the aforementioned objects for example) and a control or monitoring unit.

In this connection, the mechanical protection of the electronic component provided by the present invention can, in each case, be perceived as being the matter of fundamental importance.

In accordance with a particularly inventive embodiment, the

label is self-adhesive. The label can thereby be attached at any time to an object, goods requiring protection against theft for example, or on the windscreen of a motor vehicle. To this end, one recommendation would be that the label be  
5 at least partially provided with adhesive on at least one side thereof, the adhesive preferably being of low adherency.

In order to reliably prevent as yet unused labels from  
10 undesirably sticking together due to the adhesive coating when the labels are stored or kept in stacked layers or piles, it is expedient to provide the side of the label that is coated with an adhesive with a protective foil. This  
15 protective foil is preferably siliconised so as to allow the protective foil to be easily and completely removed from the adhesive coating when the label is to be applied to an object.

As an alternative or as an addition to the previously  
20 described self-adhesive property, the label comprises, in accordance with a preferred embodiment of the present invention, at least one attachment means, which may for example, be in the form of at least one ribbon or at least one cord. It is advantageous here, if the label is in the  
25 form of a tag.

In dependence on the intended field of use, the synthetic material may be transparent or coloured. Particular  
30 aesthetic expectations can thereby be taken into account in every case without the whole visual impression being disturbed in any way by the label.

As regards the synthetic material in which the electronic component is cast, this may, to particular advantage,  
35 comprise at least one polyurethane resin i.e. a resin based

on polyurethanes. Polyurethane resins are obtained predominantly from air-drying oils (triglycerides, unsaturated fatty acids) which are initially doubly decomposed using glycerine into a mixture of monoglycerides and diglycerides. The products resulting thereby are then converted into products, which no longer contain isocyanate groups and which dry and set like alkyd resins by virtue of an air oxidation process, using diisocyanates, preferably toluene diisocyanates (TDI) whereby the molecular ratio between isocyanate groups and hydroxy groups is less than or equal to one.

Polyurethane resins may be produced alternatively, from diisocyanates and polyalcohols (for example, glycerine, pentaerythrite) which have been partially esterified using unsaturated acids (for example, using tall oil). These are superior to the usual alkyd resins as regards drying speed and resistance to hydrolysis.

Finally, polyurethane prepolymers having terminal free or blocked isocyanate groups, which harden due to the effects of moisture and may be thermally activated if necessary, are also to be reckoned amongst the polyurethane resins.

As already mentioned above, the polyurethane resin preferably comprises the components, isocyanate and polyol.

In regard to the manufacture of labels in accordance with the present invention, two variants are basically conceivable, whereby in the first, the label is formed by flowing liquid polyurethane resin from a nozzle and then casting the electronic component in the liquid polyurethane resin. It is advantageous hereby if the flow and casting processes take the form of a drip process.

As an alternative thereto, the label may be formed by casting the electronic component in liquid polyurethane resin in a mould, whereby the mould preferably has a smoothed surface. To this end, the mould may be polished and/or lined with silicon.

In accordance with one advantageous embodiment of the present invention, the label comprises a support layer preferably consisting of synthetic material or paper which is optionally transparent or coloured and/or which may be provided with at least one imprint whereby the imprint may for example, provide information regarding the usage or the function of the label.

If the label in accordance with the present invention is coated with an adhesive as was proposed in an embodiment hereinabove, then the support layer may be provided between the synthetic material and the adhesive.

In accordance with a particularly inventive development of the present label, there is provided at least one electroluminescent device which is suppliable with energy in appropriate manner via at least one antenna and/or at least one battery. As an alternative or in addition thereto, the colour and/or the shape of the illuminated region of the electroluminescent device may be controllable by means of a remote data transmission.

The electroluminescent device advantageously comprises at least one electroluminescent dyestuff which, for example, luminesces in colour in an alternating electrical field between the plates of a capacitor. In accordance with one expedient embodiment, the electroluminescent dyestuff is applied by printing, preferably being imprinted on the support layer of the label.

In dependence on the use to which the label is put, the electronic component may, for example, be an antenna, a battery, a chip, a capacitor, a digital circuit element, a circuit, a printed oscillatory circuit, a solar cell, a coil, a power storage means and/or a transponder.

It is advantageous if the label in accordance with the present invention has a rectangular shape and/or is very thin, whereby this last mentioned property is of especial significance when the label is in the form of a security label for goods. In this case, it is of basic importance that the label should not wear out.

A multiplicity of other applications of use for the labels in accordance with the present invention is conceivable. By way of example, mention will just be made here, of the employment of the label as a part of a toll deducting system, in which case the label would preferably be arranged on the windscreen of a motor vehicle.

Further, embodiments, features and advantages of the present invention will be explained in more detail hereinafter with the aid of the embodiments illustrated by way of example in Figures 1 and 2 of the drawing. Therein

Figure 1 shows a first embodiment of a label in accordance with the present invention in the form of a sectional view; and

Figure 2 shows a second embodiment of a label in accordance with the present invention in the form of a sectional view.

Identical references in Figures 1 and 2 refer to the same or similar parts or features.



The label shown in Figures 1 and 2 is not only utilised in theft prevention systems but is also utilised for locating and/or detecting the presence or absence of an object for example, such as when one is faced with determining the current location of an object that is being sought. Here, objects with which a label of this type can be employed and on which the label is placed or to which the label is applied may perhaps be files, rubbish containers or palettes that present a logistical problem which can be solved by the present invention in an advantageous manner.

In addition, the label illustrated in Figures 1 and 2 is also suitable for use in a system for storing and transmitting data in non-contact making manner between an object (one of the aforementioned objects for example) and a control or monitoring unit.

In this connection, the mechanical protection of the electronic component 2 provided by the label illustrated in Figures 1 and 2 can, in each case, be perceived as being the matter of fundamental importance as will be explained hereinafter. Although this cannot be explicitly derived from the illustration in Figures 1 and 2, it should be mentioned here that the label is rectangular and very thin.

A first embodiment of a label in accordance with the present invention is illustrated in Figure 1 in the form of a sectional view.

The label comprises an electronic component 2 which is cast in synthetic material 1. In dependence on the use to which the label is put, the electronic component 2 may, for example, be an antenna, a battery, a chip, a capacitor, a digital circuit element, a circuit, a printed oscillatory

circuit, a solar cell, a coil, a power storage means or a transponder.

Furthermore, as is apparent from Figure 1, the label is self-adhesive. The label can thereby be applied to an object at any time. To this end, the label is provided with an adhesive 4 of low adherency on its lower surface i.e. on the side thereof facing the object.

The synthetic material 1 is transparent. As regards the synthetic material 1 in which the electronic component is cast, this is a polyurethane resin i.e. a resin based on polyurethanes. Polyurethane resins are obtained predominantly from air-drying oils (triglycerides, unsaturated fatty acids) which are initially doubly decomposed using glycerine into a mixture of monoglycerides and diglycerides. The products resulting thereby are then converted into products, which no longer contain isocyanate groups and which dry and set like alkyd resins by virtue of an air oxidation process, using diisocyanates, preferably toluene diisocyanates (TDI) whereby the molecular ratio between isocyanate groups and hydroxy groups is less than or equal to one. As already mentioned above, the polyurethane resin preferably comprises the components, isocyanate and polyol.

The manufacture of the label illustrated with the aid of Figure 1 is effected by casting the electronic component 2 in liquid polyurethane resin in a mould, whereby the mould preferably has a smoothed surface. To this end, the mould may be polished and lined with silicon.

A second embodiment of a label in accordance with the present invention is illustrated in Figure 2 in the form of a sectional view, this differing from the first embodiment

of Figure 1 basically in that the label comprises a coloured support layer 3. Here, the support layer 3 is provided between the synthetic material 1 and the adhesive 4 which covers portions of the lower surface i.e. the side of the support layer 3 remote from the synthetic material 1.

In the illustration of Figure 2, an electroluminescent device 5 that is suppliable with energy via an antenna 6 is provided on the upper surface i.e. on the side of the support layer 3 facing the synthetic material 1. Here, the colour of the illuminated region of the electroluminescent device 5 is controllable by means of a remote data transmission.

The electroluminescent device 5 comprises an electroluminescent dyestuff which lights up in colour in an alternating electrical field between the plates of a capacitor. Here, the electroluminescent dyestuff is imprinted on the support layer 3 of the label.

Claims

- 5 1. Label comprising at least one electronic component (2), characterised in that the electronic component (2) is cast in synthetic material (1).
2. Label in accordance with Claim 1, characterised in that the label is self-adhesive.
- 10 3. Label in accordance with Claim 2, characterised in that the label is at least partially provided with adhesive (4) on at least one side.
- 15 4. Label in accordance with Claim 3, characterised in that the adhesive (4) is of low adherency.
- 20 5. Label in accordance with at least one of the Claims 2 to 4, characterised in that the side of the label coated with adhesive is provided with a protective foil.
6. Label in accordance with Claim 5, characterised in that the protective foil is siliconised.
- 25 7. Label in accordance with at least one of the Claims 1 to 6, characterised in that the label comprises at least one attachment means.
- 30 8. Label in accordance with Claim 7, characterised in that the attachment means comprises at least one ribbon or at least one cord.
9. Label in accordance with at least one of the Claims 1 to 8, characterised in that the label is in the form of a tag.
- 35 10. Label in accordance with at least one of the Claims 1 to

9, characterised in that the synthetic material (1) is transparent.

5 11. Label in accordance with at least one of the Claims 1 to 9, characterised in that the synthetic material (1) is coloured.

10 12. Label in accordance with at least one of the Claims 1 to 11, characterised in that the synthetic material (1) comprises at least one polyurethane resin.

15 13. Label in accordance with Claim 12, characterised in that the polyurethane resin comprises the components, isocyanate and polyol.

20 14. Label in accordance with Claim 12 or 13, characterised in that the label is formed by flowing liquid polyurethane resin from a nozzle and by casting the electronic component (2) in the liquid polyurethane resin.

15. Label in accordance with Claim 14, characterised in that the flow and casting processes occur in the form of a drip process.

25 16. Label in accordance with Claim 12 or 13, characterised in that the label is formed by casting the electronic component (2) in the liquid polyurethane resin in a mould.

30 17. Label in accordance with Claim 16, characterised in that the mould has a smoothed surface.

18. Label in accordance with Claim 16 or 17, characterised in that the mould is polished.

35 19. Label in accordance with at least one of the Claims 16

to 18, characterised in that the mould is lined with silicon.

5 20. Label in accordance with at least one of the Claims 1 to 19, characterised in that the label comprises a support layer (3).

21. Label in accordance with Claim 20, characterised in that the support layer (3) is transparent.

10 22. Label in accordance with Claim 20, characterised in that the support layer (3) is coloured.

15 23. Label in accordance with at least one of the Claims 20 to 22, characterised in that the support layer (3) is provided with at least one imprint.

20 24. Label in accordance with at least one of the Claims 20 to 23, characterised in that the support layer (3) consists of synthetic material or paper.

25 25. Label in accordance with at least one of the Claims 2 to 6 and in accordance with at least one of the Claims 20 to 24, characterised in that the support layer (3) is provided between the synthetic material (2) and the adhesive (4).

30 26. Label in accordance with at least one of the Claims 1 to 25, characterised in that at least one electroluminescent device (5) is provided.

27. Label in accordance with Claim 26, characterised in that the electroluminescent device (5) is suppliable with energy via at least one antenna (6) and/or at least one battery.

35 28. Label in accordance with Claim 26 or 27, characterised

in that the colour and/or the shape of the illuminated region of the electroluminescent device (5) is controllable by means of a remote data transmission.

5 29. Label in accordance with at least one of the Claims 26 to 28, characterised in that the electroluminescent device (5) comprises at least one electroluminescent dyestuff.

10 30. Label in accordance with Claim 29, characterised in that the electroluminescent dyestuff is applied by printing.

15 31. Label in accordance with at least one of the Claims 20 to 24 and in accordance with Claim 29 or 30, characterised in that the electroluminescent dyestuff is imprinted on the support layer (3).



20 32. Label in accordance with at least one of the Claims 1 to 31, characterised in that the electronic component (2) is an antenna, a battery, a chip, a capacitor, a digital circuit element, a circuit, a printed oscillatory circuit, a solar cell, a coil, a power storage means and/or a transponder.

25 33. Label in accordance with at least one of the Claims 1 to 32, characterised in that the label has a rectangular shape.

34. Label in accordance with at least one of the Claims 1 to 33, characterised in that the label is very thin.

30 35. Label in accordance with at least one of the Claims 1 to 34, characterised in that the label is in the form of a security label for goods.

35 36. Label in accordance with at least one of the Claims 1 to 34, characterised in that the label forms part of a toll deducting system.

**Fig. 1****Fig. 2**



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/07571

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G09F3/18 G06K19/077

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G09F G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 512 543 A (NIPPON DENSO CO) 11 November 1992 (1992-11-11)  column 10, line 44 -column 11, line 28 column 14, line 29-33 column 15, line 45 -column 16, line 16 column 17, line 11-29 column 37, line 10-37; figures 1,9,13-15,34A,34B  ---	1-3,5-7, 9,20, 23-25, 32,35
X	FR 2 704 964 A (DIET JEAN PAUL) 10 November 1994 (1994-11-10) page 1, line 1-3 page 2, line 4-17 page 4, line 20 -page 5, line 10; figures 1-3  ---  -/--	1,7,8, 32-35

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 January 2000

Date of mailing of the international search report

02/02/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Jandl, F

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/07571

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 767 503 A (GLOTON JEAN-PIERRE) 16 June 1998 (1998-06-16)</p> <p>column 3, line 24 -column 4, line 21 column 5, line 1-37; figures 1-3 ---</p>	<p>1, 12, 14, 16-18, 20, 32-34</p>
A	<p>US 5 153 842 A (CHEN ROBERT ET AL) 6 October 1992 (1992-10-06)</p> <p>column 3, line 9-33 column 5, line 48 -column 6, line 38 column 7, line 35-52 -----</p>	<p>1-3, 7, 9, 10, 20, 24-28, 32-35</p>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/07571

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0512543 A	11-11-1992	JP 2830501 B	02-12-1998
		JP 4333415 A	20-11-1992
		JP 2890886 B	17-05-1999
		JP 4341414 A	27-11-1992
		JP 4345421 A	01-12-1992
		JP 2893995 B	24-05-1999
		JP 4345422 A	01-12-1992
		JP 4345423 A	01-12-1992
		JP 4345424 A	01-12-1992
		JP 2973582 B	08-11-1999
		JP 4350016 A	04-12-1992
		JP 4354721 A	09-12-1992
		JP 4354722 A	09-12-1992
		JP 2894002 B	24-05-1999
		JP 4361915 A	15-12-1992
		JP 4359183 A	11-12-1992
		JP 4367293 A	18-12-1992
		JP 2606183 B	30-04-1997
		JP 5142342 A	08-06-1993
		AU 662901 B	21-09-1995
		AU 1602892 A	12-11-1992
		DE 69228144 D	25-02-1999
		DE 69228144 T	23-09-1999
		JP 2830885 B	02-12-1998
		JP 5139530 A	08-06-1993
		US 5557096 A	17-09-1996
		US 5340968 A	23-08-1994
		JP 5170331 A	09-07-1993
		JP 5217587 A	27-08-1993
-----			
FR 2704964 A	10-11-1994	NONE	
-----			
US 5767503 A	16-06-1998	FR 2724477 A	15-03-1996
		DE 69505481 D	26-11-1998
		EP 0709804 A	01-05-1996
		JP 8090971 A	09-04-1996
-----			
US 5153842 A	06-10-1992	NONE	